



SCHEDULE OF SLABS

SLAB MARK	THICKNESS	TYPE	REINFORCEMENT STEEL AT	
			SHORT SPAN	LONG SPAN
S1	5"	↕	8Ø @ 5" C/C	8Ø @ 6" C/C
S2	5"	↕	8Ø @ 6" C/C	8Ø @ 7" C/C
S3	5"	↔	8Ø @ 5" C/C	8Ø @ 8" C/C

General Notes : --

1. Use M20 (1:1.5:3) for slab & Beams
2. Use FE 500 grade tor steel.
3. Provide clear cover of 1" for beams $\frac{3}{4}$ " slab
4. Read horizontal beam from left to right & vertical beam from bottom to top.
5. crank +ve bars at L/4 th of span & extend -ve bars L/5 th of span.
6. Do not over lap bottom rods at center and top rods at support.

GOOD FOR CONSTRUCTIONS

Client: MODI PROPERTIES & INVESTMENTS PVT.LTD
 Project: MIRYALGUDA - A1 (3 BHK)
 Architects: Architectural Associates
 Structural Consultant: KULKARNI CONSULTANT'S

DATE: 30-08-2017
 DEALT BY: PAWAN
 DESIGN BY: SANTOSH
 CHECKED BY: KULKARNI

TITLE: FIRST FLOOR SLAB & BEAM DETAILS
 DWG. NO: KC/MG/SD/A1/3