



SCHEDULE OF SLABS				
SLAB MARK	THICKNESS	TYPE	REINFORCEMENT STEEL AT	
			SHORT SPAN	LONG SPAN
S1	5"	↕	8Ø @ 5" C/C	8Ø @ 6" C/C
S2	5"	↕	8Ø @ 6" C/C	8Ø @ 7" C/C

- General Notes : --
1. Use M20 (1:1.5:3) for slab & Beams
 2. Use FE 500 grade tor steel.
 3. Provide clear cover of 1" for beams & 3/4" slab
 4. Read horizontal beam from left to right & vertical beam from bottom to top.
 5. crank +ve bars at L/4 th of span & extend -ve bars L/5 th of span.
 6. Do not over lap bottom rods at center and top rods at support.

GOOD FOR CONSTRUCTIONS

Client: MODI PROPERTIES & INVESTMENTS PVT.LTD

Project: MIRYALGUDA - A1 (3 BHK)

Architects: Architectural Associates
8-1-383, R. P. Road, Secunderabad-3
subashanandagar@hotmail.com

STRUCTURAL CONSULTANT: KULKARNI CONSULTANT'S
STRUCTURAL ENGINEERS, ARCHITECTS & PROJECT CONSULTANTS
#216, KIBBERA TOWERS, NARAYAN GUDA, HYDERABAD
CONTACT NO'S: 05023223891, 09246343724, 09246343720

DATE: 30-08-2017 TYPE - A1 - 3 BHK

DESIGN BY: PAWAN TITLE: GROUND FLOOR SLAB & BEAM DETAILS

CHECKED BY: SANTOSH

APPROVED BY: KULKARNI DWG. NO: KC/MG/SD/A1/2 REV. No: