


- General Notes :-**
1. Use M25 (1:1:2) grade for columns & M20 (1:1.5:3) for footings, slab & Beams
 2. Use FE 500 grade tor steel.
 3. Provide clear cover of 2" for footings & 1.5" for columns.
 4. S.B.C of the Soil is taken as 250kn/m2.
 5. Footings are design for Ground & Upeer 2 floor.
 6. Provide clear cover of 1" for beams
 7. Read horizontal beams from left to right & vertical from bottom to left.
 8. crank +ve bars at L/4 th of span & extend -ve bars L/5 th of span.
 9. Do not over lap bottom rods at center and top rods at support.
 10. Slab thickness

DESCRIPTION	DATE

GOOD FOR CONSTRUCTIONS

Client	MODI PROPERTIES & INVESTMENTS PVT.LTD
Project	MIRYALGUDA
STRUCTURAL CONSULTANT	 KULKARNI CONSULTANT'S STRUCTURAL ENGINEERS, ARCHITECTS & PROJECT CONSULTANT'S #216, KUBERA TOWER'S, NARAYAN GUDA, HYDERABAD. CONTACT NO'S:- 04023223891, 09246343724, 09246343720.

DATE	15-02-2017	TYPE - A1 (DUPLEX)	
DEALT BY	PAWAN	TITLE:	FIRST FLOOR SLAB DETAILS
DESIGN BY	VIKUAR		
CHECKED & APPROVED :	KULKARNI	DWG. NO.	KC/SD/A1/12
		REV. No.	1