



General Notes : --

1. Use M20 (1:1.5:3) for slab & Beams
2. Use FE 500 grade tor steel.
3. Provide clear cover of 1" for beams  $\frac{3}{4}$ " slab
4. Read horizontal beam from left to right & vertical beam from bottom to top.
5. crank +ve bars at L/4 th of span & extend -ve bars L/5 th of span.
6. Do not over lap bottom rods at center and top rods at support.

PRODUCED BY AN AUTODESK STUDENT VERSION

PRODUCED BY AN AUTODESK STUDENT VERSION

DESCRIPTION		DATE
Client	MODI PROPERTIES & INVESTMENTS PVT.LTD	
Project	MIRYALGUDA - A2 ( 3 BHK )	
Architects	<b>Architectural Associates</b> ARCHITECTS & INTERIOR DESIGNERS 8-1-383, R. P. Road, Secunderabad-3 subashanandsagar@hotmail.com	
STRUCTURAL CONSULTANT	<b>KULKARNI CONSULTANT'S</b> STRUCTURAL ENGINEERS, ARCHITECTS & PROJECT CONSULTANT'S #216, KUBERA TOWER'S, NARAYAN GUDA, HYDERABAD. CONTACT NO'S:- 04023223891, 09246343724, 09246343720.	
DATE	17-11-2017	TYPE - A2 - 3 BHK
DEALT BY	PAWAN	TITLE: STAIRCASE HEAD ROOM SLAB & BEAM DETAILS
DESIGN BY	SANTOSH	
CHECKED & APPROVED	KULKARNI	DWG. NO. KC/MG/SD/A1/3
		REV. No.