



- General Notes :-**
1. Use M25 (1:1:2) grade for columns & M20 (1:1.5:3) for footings, slab & Beams
 2. Use FE 500 grade tor steel.
 3. Provide clear cover of 2" for footings & 1.5" for columns.
 4. S.B.C of the Soil is taken as 250kn/m².
 5. Footings are designen for Ground & Upeer 2 floor.
 6. Provide clear cover of 1"for beams
 7. Read horizontal beams from left to right & vertical from bottom to left.
 8. crank +ve bars at L/4 th of span & extend -ve bars L/5 th of span.
 9. Do not over lap bottom rods at center and top rods at support.
 10. Slab thickness

DESCRIPTION	DATE

GOOD FOR CONSTRUCTIONS

Client	MODI PROPERTIES & INVESTMENTS PVT.LTD
Project	MIRYALGUDA

STRUCTURAL CONSULTANT

KULKARNI CONSULTANT'S
STRUCTURAL ENGINEERS, ARCHITECTS & PROJECT CONSULTANT'S
#216, KUBERA TOWER'S, NARAYAN GUDA, HYDERABAD.
CONTACT NO'S:- 04023223891, 09246343724, 09246343720.

DATE	12-01-2017	TYPE - A2 (DUPLEX)	
DEALT BY	PAWAN	TITLE:	FIRST FLOOR SLAB DETAILS
DESIGN BY	VIKJAR		
CHECKED & APPROVED:	KULKARNI	DWG. NO.	KC/SD/A2/20
		REV. No.	1