



- General Notes :-**
1. Use M25 (1:1:2) grade for columns & M20 (1:1.5:3) for footings, slab & Beams
 2. Use FE 500 grade tor steel.
 3. Provide clear cover of 2" for footings & 1.5" for columns.
 4. S.B.C of the Soil is taken as 250kn/m2.
 5. Footings are design for Ground & Upeer 2 floor.
 6. Provide clear cover of 1" for beams
 7. Read horizontal beams from left to right & vertical from bottom to left.
 8. crank +ve bars at L/4 th of span & extend -ve bars L/5 th of span.
 9. Do not over lap bottom rods at center and top rods at support.
 10. Slab thickness

| DESCRIPTION | DATE |
|-------------|------|
| | |
| | |
| | |
| | |

GOOD FOR CONSTRUCTIONS

| | | | |
|------------------------------|--|--|--|
| Client | MODI PROPERTIES & INVESTMENTS PVT.LTD | | |
| Project | MIRYALGUDA | | |
| STRUCTURAL CONSULTANT | KULKARNI CONSULTANT'S STRUCTURAL ENGINEERS, ARCHITECTS & PROJECT CONSULTANT'S #216, KUBERA TOWER'S, NARAYAN GUDA, HYDERABAD. CONTACT NO'S:- 04023223891, 09246343724, 09246343720. | | |

| | | | |
|---------------------------------|------------|---------------------------|----------------------------------|
| DATE | 12-01-2017 | TYPE - A2 (DUPLEX) | |
| DEALT BY | PAWAN | TITLE: | GROUND FLOOR SLAB DETAILS |
| DESIGN BY | VIKUAR | | |
| CHECKED & APPROVED : | KULKARNI | DWG. NO. | KC/SD/A2/18 |
| | | | REV. No. |
| | | | 1 |