

**General Notes :-**


1. Use M20 (1:1.5:3) for slab & Beams
2. Use FE 500 grade tor steel.
3. Provide clear cover of 1"for beams &  $\frac{3}{4}$ "slab
4. Read horizontal beam from left to right & vertical beam from bottom to top.
5. crank +ve bars at L/4 th of span & extend -ve bars L/5 th of span.
6. Do not over lap bottom rods at center and top rods at support.


DESCRIPTION	DATE



Client	MODI PROPERTIES & INVESTMENTS PVT.LTD
--------	--

Project	MIRYALGUDA - (CLUB HOUSE)
---------	---------------------------

STRUCTURAL CONSULTANT	 <b>KULKARNI CONSULTANT'S</b> STRUCTURAL ENGINEERS, ARCHITECTS & PROJECT CONSULTANT'S #216, KUBERA TOWER'S, NARAYAN GUDA, HYDERABAD. CONTACT NO'S:- 04023223891, 09246343724, 09246343720.
-----------------------	--

DATE	14-8-2017	MIRYALGUDA (CLUB HOUSE)	
DEALT BY	PAWAN	TITLE:	TYPICAL FLOOR SLAB DETAILS
DESIGN BY	SANTOSH		
CHECKED & APPROVED:	KULKARNI	DWG. NO.	KC/SD/M/CH/5
		REV. No.	0