



- General Notes :--
1. Use M25 (1:1:2) grade for columns & M20 (1:1.5:3) for footings, slab & Beams
  2. Use FE 500 grade tor steel.
  3. Provide clear cover of 2" for footings & 1.5" for columns.
  4. S.B.C of the Soil is taken as 200kn/m2.
  5. Provide clear cover of 1"for beams
  6. All loose pockets should be filled by p.c.c (1:2:4).
  7. Rock foundation should have anchor rods in the rock .

PRODUCED BY AN AUTODESK STUDENT VERSION

PRODUCED BY AN AUTODESK STUDENT VERSION

DESCRIPTION	DATE

FOR REFERENCE

Client: MODI PROPERTIES & INVESTMENTS PVT.LTD

Project: MIRYALGUDA - ENTRENCE ATCH

STRUCTURAL CONSULTANT **KULKARNI CONSULTANT'S**  
 STRUCTURAL ENGINEERS, ARCHITECTS & PROJECT CONSULTANT'S  
 #216, KUBERA TOWER'S, NARAYAN GUDA, HYDERABAD.  
 CONTACT NO'S:- 04023223891, 09246343724, 09246343720.

DATE	8-11-2017	TITLE: ARCH DETAILS	DWG. NO. KC/MG/SD/2	REV. No. 1
DEALT BY	PAWAN			
DESIGN BY	SANTOSH			
CHECKED & APPROVED	KULKARNI			