



- GENERAL NOTES**
- USE M25 (1:1.5:2) GRADE CONCRETE FOR COLUMNS & M20 (1:1.5:3) FOR BEAMS & SLAB
 - USE FE 500 GRADE TOR STEEL.
 - PROVIDE CLEAR COVER OF 1.5" FOR COLUMNS , 1"FOR BEAMS & 3/4" FOR SLAB
 - PROVIDE 1" CAMBER AT FREE END FOR CANTILEVER BEAMS & SLABS.
 - IN SLAB EXTEND -VE STEEL UPTO 0.30L FROM FACE OF SUPPORT.
 - DO NOT PROVIDE EXTRA REINFORCEMENT AT SIMPLY SUPPORTS.
 - LAP LENGTH 48 D (D-IS THE DIA OF THE BAR) IN COMPRESSION.
 - LAP LENGTH 52 D (D-IS THE DIA OF THE BAR) IN TENSION.
 - ONLY FIGURED DIMENSIONS SHALL BE FOLLOWED.
 - ALL THE DIMENSIONS ARE IN INCHES & FEET.
 - DO NOT SCALE THE DRAWING.
 - REFER ARCHITECT DRAWING FOR CENTER LINE DIMENSIONS.

GOOD FOR CONSTRUCTIONS

Ownters & Developers:		5-4-187 /3&4,Soham mansarovar,II Floor, K.G. Road, Sector-30, Gurgaon, Haryana	
Architects & Engineers:		KULKARNI CONSULTANTS STRUCTURAL ENGINEERS, ARCHITECTS & PROJECT CONSULTANTS #216, KUBERA TOWERS, WAKHANI COLONY, HYDERABAD, ANDHRA PRADESH, INDIA. 9959323291, 9959323292, 9959323293	
SCALE:	N.T.S	VISTA HOMES BLOCK - (D)	
DATE:	7-11-17	TITLE:	CELLAR BEAM DETAILS
DRAWN:	PAWAN	DWG. NO.:	KC/WH/SD/D/9
CHECKED:	KULKARNI	SH. NO.1	
APPROVED:		REV. NO.	0