



- GENERAL NOTES**
1. USE M25 (1:1.5:2) GRADE CONCRETE FOR COLUMNS & M20 (1:1.5:3) FOR BEAMS & SLAB
 2. USE FE 500 GRADE TOR STEEL.
 3. PROVIDE CLEAR COVER OF 1.5" FOR COLUMNS , 1"FOR BEAMS & 3/4" FOR SLAB
 4. PROVIDE 1" CAMBER AT FREE END FOR CANTILEVER BEAMS & SLABS.
 5. IN SLAB EXTEND -VE STEEL UPTO 0.30L FROM FACE OF SUPPORT.
 6. DO NOT PROVIDE EXTRA REINFORCEMENT AT SIMPLY SUPPORTS.
 7. LAP LENGTH 48 D (D-IS THE DIA OF THE BAR) IN COMPRESSION.
 8. LAP LENGTH 52 DC D- IS THE DIA OF THE BAR) IN TENSION.
 9. ONLY FIGURED DIMENSIONS SHALL BE FOLLOWED.
 10. ALL THE DIMENSIONS ARE IN INCHES & FEET.
 11. DO NOT SCALE THE DRAWING.
 12. REFER ARCHITECT DRAWING FOR CENTER LINE DIMENSIONS.

GOOD FOR CONSTRUCTIONS



Ownters & Developers:

VISTA HOMES BLOCK - (D)

Architects & Engineers:

KULKARNI CONSULTANTS
 STRUCTURAL ENGINEERS, ARCHITECTS & PROJECT CONSULTANTS
 #210, KUMBHAR TOWERS, MARAKANI COLONY, THEREDANG, KOLHAPUR, MAHARASHTRA, INDIA
 CONTACT NO: 9823243971, 9823243972, 9823243973

SCALE	N.T.S	TITLE	CELLAR BEAM DETAILS
DATE:	7-11-17	DWG. NO.	KC/HH/SD/D/11
DRAWN:	PAWAN	REV. NO.	0
CHECKED:			
APPROVED:	KULKARNI		