



SECOND FLOOR SLAB PROJECTIONS

GENERAL NOTES

- USE M25 (1:1.5:2) GRADE CONCRETE FOR COLUMNS & M20 (1:1.5:3) FOR BEAMS & SLAB
- USE FE 500 GRADE TOR STEEL.
- PROVIDE CLEAR COVER OF 1.5" FOR COLUMNS, 1" FOR BEAMS & 3/4" FOR SLAB
- PROVIDE 1" CAMBER AT FREE END FOR CANTILEVER BEAMS & SLABS.
- IN SLAB EXTEND -VE STEEL UPTO 0.30L FROM FACE OF SUPPORT.
- DO NOT PROVIDE EXTRA REINFORCEMENT AT SIMPLY SUPPORTS.
- LAP LENGTH 48 D (D- IS THE DIA OF THE BAR) IN COMPRESSION.
- LAP LENGTH 52 D (D- IS THE DIA OF THE BAR) IN TENSION.
- ONLY FIGURED DIMENSIONS SHALL BE FOLLOWED.
- ALL THE DIMENSIONS ARE IN INCHES & FEET.
- DO NOT SCALE THE DRAWING.
- REFER ARCHITECT DRAWING FOR CENTER LINE DIMENSIONS.

REV. No.	DESCRIPTION	DATE
1		



Owners & Developers: _____
 5-4-187 /3&4, Soham mansion, II Floor, M.G. Road, Secunderabad-500003.
 Phone:66335551(4lines) Fax:040-27544058
 E-mail :info @modiproperties.com

Architects & Engineers: **KULKARNI CONSULTANTS**
 STRUCTURAL ENGINEERS, ARCHITECTS & PROJECT CONSULTANTS
 #216, KUBERA TOWER'S, NARAYAN GUDA, HYDERABAD.
 CONTACT NO'S:- 04023223891, 09246343724, 09246343720.

SCALE:	N.T.S	VISTA HOMES BLOCK - (D)
DATE:	14-12-17	
DRAWN:	PAWAN	
CHECKED & APPROVED:	KULKARNI	
TITLE:	SECOND FLOOR slab projections	
DWG. NO.	KC/VH/SD/D/	REV. No. 0