



GENERAL NOTES

1. USE M25 (1:1.5:2) GRADE CONCRETE FOR COLUMNS & M20 (1:1.5:3) FOR BEAMS & SLAB
2. USE FE 500 GRADE TOR STEEL.
3. PROVIDE CLEAR COVER OF 1.5" FOR COLUMNS , 1" FOR BEAMS & 3/4" FOR SLAB
4. PROVIDE 1" CAMBER AT FREE END FOR CANTILEVER BEAMS & SLABS.
5. IN SLAB EXTEND -VE STEEL UPTO 0.30L FROM FACE OF SUPPORT.
6. DO NOT PROVIDE EXTRA REINFORCEMENT AT SIMPLY SUPPORTS.
7. LAP LENGTH 48 D (D-IS THE DIA OF THE BAR) IN COMPRESSION.
8. LAP LENGTH 52 D (D-IS THE DIA OF THE BAR) IN TENSION.
9. ONLY FIGURED DIMENSIONS SHALL BE FOLLOWED.
10. ALL THE DIMENSIONS ARE IN INCHES & FEET.
11. DO NOT SCALE THE DRAWING.
12. REFER ARCHITECT DRAWING FOR CENTER LINE DIMENSIONS.

GOOD FOR CONSTRUCTIONS



Owners & Developers:

5-4-187 /3&4, Soham mansarovar, IT Floor,
 K.G. Road, Sion, Mumbai-400022,
 Phone: 25521414 (lines) Fax: 25544058
 E-mail: info@noidiproperties.com

Architects & Engineers:

KULKARNI CONSULTANTS
 STRUCTURAL ENGINEERS, ARCHITECTS & PROJECT CONSULTANTS
 #216, KUBERA TOWERS, MARANI COLONY, MUMBAI,
 CONTACT NO: 25522552, 25522552, 25522552

SCALE	N.T.S	TITLE	VISTA HOMES BLOCK - (D)
DATE:	9-12-17	CHECKED	SH. NO.2
DRAWN:	PAWAN	APPROVED	REV. NO.
DWC. NO.	KC/H/5D/D/15		0