



NOTE :

1. DEPTH OF BRICKWORK TO BE INCREASED/ DECREASED DEPENDING ON LOOSE OR HARD SOIL.
2. PLINTH BEAM IS A MUST UNDER EACH & EVERY WALL.
3. STAIRCASE SLAB TO START FROM PLINTH BEAM.
4. INTERNAL PLINTH BEAM CAN ONLY HAVE 1 LAYER OF CEMENT BLOCK OR, JUST P.C.C LAYER (2" OR 4") IF SOIL CONDITIONS PERMIT.
5. IN CASE PLINTH BEAM IS NOT CASTED UNDER A WALL (IN CASE OF MISTAKE OR ADDITIONS & ALTERATIONS), MAKE A 30" DEEP CRS WALL WITH 4" P.C.C. AND 3" D.P.C. UNDER THE WALL.


APPROVED BY
 13 OCT 2017
 SURESH MODI
 MANAGING DIRECTOR

| Description | Direction | Owners & Developers : | Date : | 13/10/2017 | Promoted by |
|---|---|---------------------------|---------------|--------------|--------------------------|
| STANDARD DRAWING FOR BRICK-WORK UNDER PLINTH BEAM |  | Modi Properties Pvt. Ltd. | Prepared by : | Madhav Bhatt | Modi Properties Pvt. Ltd |
| | | Project Name & Phase : | Approved by : | Soham Modi | Phone:+91-40-6633555; |
| | | | Scale : | N.T.S | |