



General Notes : --

1. Use M25 (1:1:2) grade for columns & M20 (1:1.5:3) for footings, slab & Bams
2. Use FE415 grade for steel.
3. Provide clear cover of 2" for footings & 1.5" for columns.
4. S.B.C of the Soil is taken as 400kn/m2.
5. Footings are design for Ground & first floor.
6. Provide clear cover of 1" for beams
7. Read horizontal beams from left to right & vertical from bottom to left.
8. Crank +ve bars at L/4 th of span & extend -ve bars L/5 th of span.
9. Do not over lap bottom rods at center and top rods at support.
10. Slab thickness

Project : --

PROPOSED RESIDENTIAL DUPLEX BANGLOWS FOR M/s. MODI **PROPERTIES** AT SHAMEERPET

Sheet Title : --

EAST FACING (Bungalow no.72) TYPE -E

COLUMN & FOOTING DETAIL'S

Drawing no: --	NORTH :-
Date : -- 30-12-17	
Scale : --	
Dealt By: -- PAWAN	
Chk by: -- M. Dattatreya rao.	

Architect's: --

Architectural Asso
8-1-383, R . P .ROAD, Sec- bad.

Consultant's: --

Kulkarni Consultant's
Stur. Engineer's & Project Consultant's
#216, Kubera Tower's, Narayan Guda, Hyd.