


- GENERAL NOTES**
1. USE M25 (1:1.5:2) GRADE CONCRETE FOR BEAMS & SLAB
  2. USE F500 GRADE TOR STEEL.
  3. PROVIDE CLEAR COVER OF 1.5" FOR COLUMNS, 1" FOR BEAMS & 3/4" FOR SLAB
  4. PROVIDE 1" CAMBER AT FREE END FOR CANTILEVER BEAMS & SLABS.
  5. IN SLAB EXTEND -VE STEEL UPTO 0.30L FROM FACE OF SUPPORT.
  6. DO NOT PROVIDE EXTRA REINFORCEMENT AT SIMPLY SUPPORTS.
  7. LAP LENGTH 48 D (D- IS THE DIA OF THE BAR) IN COMPRESSION.
  8. LAP LENGTH 52 D (D- IS THE DIA OF THE BAR) IN TENSION.
  9. ONLY FIGURED DIMENSIONS SHALL BE FOLLOWED.
  10. ALL THE DIMENSIONS ARE IN INCHES & FEET.
  11. DO NOT SCALE THE DRAWING.
  12. REFER ARCHITECT DRAWING FOR CENTER LINE DIMENSIONS.

DETAILS HOLD UPTO NEXT DRAWINGS

<b>Owners &amp; Developers:</b>		B-4-187 / 384, Saham mansion, II Floor, M.G. Road, Secundersabad-500083. Phone: 66338851 (4lines) Fax: 040-27844088 E-mail: info@modiproperties.com	
<b>Architects &amp; Engineers:</b>		 <b>KULKARNI CONSULTANT'S</b> STRUCTURAL ENGINEERS, ARCHITECTS & PROJECT CONSULTANTS #216, KUBERA TOWERS, NARAYAN GUDA, HYDERABAD. CONTACT NO'S: 04023223891, 09246343724, 09246343720.	
<b>SCALE:</b>	N.T.S	<b>MAYFLOWER PLATNUM -- (A)</b>	
<b>DATE:</b>	27-06-2019	<b>TITLE: BASEMENT 2 BEAM DETAILS</b>	
<b>DESIGNED:</b>	SAITOBH	<b>DWG. NO.</b>	SAN/MP/SD/B/15
<b>CHECKED:</b>	KULKARNI	<b>REV. No.</b>	0