



- GENERAL NOTES**
- USE M25 (1:1.5:2) GRADE CONCRETE FOR BEAMS & SLAB
 - USE FE500 GRADE TOR STEEL.
 - PROVIDE CLEAR COVER OF 1.5" FOR COLUMNS , 1"FOR BEAMS & 3/4" FOR SLAB
 - PROVIDE 1" CAMBER AT FREE END FOR CANTILEVER BEAMS & SLABS.
 - IN SLAB EXTEND -VE STEEL UPTO 0.30L FROM FACE OF SUPPORT.
 - DO NOT PROVIDE EXTRA REINFORCEMENT AT SIMPLY SUPPORTS.
 - LAP LENGTH 48 D (D- IS THE DIA OF THE BAR) IN COMPRESSION.
 - LAP LENGTH 52 D (D- IS THE DIA OF THE BAR) IN TENSION.
 - ONLY FIGURED DIMENSIONS SHALL BE FOLLOWED.
 - ALL THE DIMENSIONS ARE IN INCHES & FEET.
 - DO NOT SCALE THE DRAWING.
 - REFER ARCHITECT DRAWING FOR CENTER LINE DIMENSIONS.

DETAILS HOLD UPTO NEXT DRAWINGS

PRODUCED BY AN AUTODESK EDUCATIONAL PRODUCT

PRODUCED BY AN AUTODESK EDUCATIONAL PRODUCT

Owners & Developers:	B-4-187 /38-A, Saham mansion, II Floor, H.G. Road, Secundersabad-500083. Phone: 66338851 (4lines) Fax: 040-27844088 E-mail: info@modiproperties.com
Architects & Engineers:	KULKARNI CONSULTANTS STRUCTURAL ENGINEERS, ARCHITECTS & PROJECT CONSULTANTS #216, KUBERA TOWER'S, NARAYAN GUDA, HYDERABAD. CONTACT NO'S:- 04023223891, 09246343724, 09246343720.
SCALE: N.T.S	MAYFLOWER PLATINUM - (A)
DATE: 27-06-2019	TITLE: BASEMENT - 2 SLAB DETAILS
DESIGNED: SANTOSH	DWG. NO. SAN/MP/SD/B/16
CHECKED & APPROVED: KULKARNI	REV. No. 0