



- General Notes : --
1. Use M25 (1:1:2) grade for columns & M20 (1:1.5:3) for footings, slab & Beams
  2. Use FE500 grade for steel.
  3. Provide clear cover of 2" for footings & 1.5" for columns.
  4. Provide clear cover of 1" for beams
  5. Read horizontal beams from left to right & vertical from bottom to left.
  6. Crank +ve bars at L/4 th of span & extend -ve bars L/5 th of span.
  7. Do not over lap bottom rods at center and top rods at support.
  8. Slab thickness

DESCRIPTION	DATE

**GOOD FOR CONSTRUCTION**

Client: MODI PROPERTIES & INVESTMENTS PVT.LTD  
 Project: NILAGIRI ESTATE AT RAMPALLY, PHASE - II  
 STRUCTURAL CONSULTANT: **KULKARNI CONSULTANT'S**  
 STRUCTURAL ENGINEERS, ARCHITECTS & PROJECT CONSULTANT'S  
 #216, KUBERA TOWER'S, NARAYAN GUDA, HYDERABAD.  
 CONTACT NO'S:- 04023223891, 09246343724, 09246343720.

DATE	30-11-2016	TYPE --AA2(SINGLE & Duplex)
DEALT BY	PAWAN	
DESIGN BY	MD VIQHAR AHMED	TITLE: STAIRCASE HEAD ROOM SLAB DETAILS
CHECKED & APPROVED	KULKARNI	
DWG. NO.	KC/SD/NS2/4	REV. No. 1

PRODUCED BY AN AUTODESK STUDENT VERSION

PRODUCED BY AN AUTODESK STUDENT VERSION