



General Notes : --

1. Use M25 (1:1:2) grade for columns &
2. Use M20 (1:1.5:3) grade for footings, slab & Beams
3. Provide clear cover of 2" for footings &
4. S.F.C for the soil is taken as 350kn/m<sup>2</sup>.
5. Footings are design for Ground & 1st
6. Provide clear cover of 1" for beams
7. Read horizontal beams from left to right &
8. vertical from bottom to left
9. crank +ve bars at L/4 th of span & extend -ve bars to 5th of span from bottom rods at center and top rods at support.
10. Slab thickness

DESCRIPTION	DATE



Client	MODI PROPERTIES & INVESTMENTS PVT.LTD		
Project	NILAGIRI ESTATE AT RAMPALLY, PHASE - II		
STRUCTURAL CONSULTANT	<b>KULKARNI CONSULTANT'S</b> STRUCTURAL ENGINEERS, ARCHITECTS & PROJECT CONSULTANTS #216, KUBERA TOWERS, NARAYAN GUDA, HYDERABAD. CONTACT NO'S:- 04023223891, 09246343724, 09246343720.		
DATE	29-5-2017	TYPE - (A1 - SINGLE), EAST FACING (80C)	
DEALT BY	PAWAN	TITLE: SLAB & BEAM DETAILS	
DESIGN BY	SRIKANTH		
CHECKED & APPROVED	KULKARNI	DWG. NO.	KC/RP/SD/3
		REV. No.	1

PRODUCED BY AN AUTODESK STUDENT VERSION

PRODUCED BY AN AUTODESK STUDENT VERSION