



SCHEDULE OF SLABS

SLAB MARK	THICK-NESS	TYPE	REINFORCEMENT STEEL AT	
			SHORT SPAN	LONG SPAN
S1	4 1/2"	↔	8Ø @ 5" C/C	8Ø @ 8" C/C
S2	4 1/2"	↕	8Ø @ 5" C/C	8Ø @ 8" C/C
S3	4 1/2"	↕↔	8Ø @ 8" C/C	8Ø @ 8" C/C

General Notes : --

1. Use M20 (1:1.5:3) grade for slabs & Beams
2. Use FE500 grade for steel.
3. Provide clear cover of 1" for beams and 3/4" for slabs
4. Read horizontal beams from left to right & vertical from bottom to left.
5. crank +ve bars at L/4 th of span & extend -ve bars L/5 th of span.
6. Do not over lap bottom rods at center and top rods at support.

REVISION	DATE
REVISED SLAB	25-05-18

Client: MODI PROPERTIES & INVESTMENTS PVT.LTD

Project: PROPOSED FARM HOUSE AT YENKAPALLY

STRUCTURAL CONSULTANT: **KULKARNI CONSULTANT'S**
 STRUCTURAL ENGINEERS, ARCHITECTS & PROJECT CONSULTANT'S
 #216, KUBERA TOWER'S, NARAYAN GUDA, HYDERABAD.
 CONTACT NO'S: 04023223891, 09246343724, 09246343720.

DATE	27-05-2018	VILLA	
DEALT BY	SANISH	TITLE:	SLAB AND BEAM DETAILS
DESIGN BY	SANTOSH		
CHECKED & APPROVED	KULKARNI	DWG. NO.	KC/FH/SD/9