



General Notes :--

1. Use M25 (1:1:2) grade for columns & M20 (1:1.5:3) for footings, slab & Beams
2. Use FE500 grade tor steel.
3. Provide clear cover of 2" for footings & 1.5" for columns.
4. S.B.C of the Soil is taken as
5. Footings are designed for Ground floor.
6. Provide clear cover of 1" for beams
7. Read horizontal beams from left to right & vertical from bottom to left.
8. Crank +ve bars at L/4 th of span & extend -ve bars L/5 th of span.
9. Do not over lap bottom rods at center and top rods at support.
10. Slab thickness

DESCRIPTION	DATE



Client	MODI PROPERTIES & INVESTMENTS PVT.LTD		
Project	PROPOSED FARM HOUSE AT YENKAPALLY		
STRUCTURAL CONSULTANT	KULKARNI CONSULTANT'S STRUCTURAL ENGINEERS, ARCHITECTS & PROJECT CONSULTANT'S #216, KUBERA TOWER'S, NARAYAN GUDA, HYDERABAD. CONTACT NOS:- 04023223891, 09246343724, 09246343720.		
DATE	7-4-2017	VILLA (PLOT NO. 46)	
DEALT BY	PAWAN	TITLE:	PLINTH BEAM DETAILS (kitchen extension)
DESIGN BY			
CHECKED & APPROVED:	KULKARNI	DWG. NO.	KC/FH/SD/7A
		REV. No.	0