



- General Notes : --
1. Use M25 (1:1:2) grade for columns & M20 (1:1.5:3) for footings, slab & Bams
 2. Use FE415 grade for steel.
 3. Provide clear cover of 2" for footings & 1.5" for columns.
 4. S.B.C of the Soil is taken as 400kn/m2.
 5. Footings are design for Ground +2ND floor
 6. Provide clear cover of 1" for beams
 7. Read horizontal beams from left to right & vertical from bottom to left.
 8. crank +ve bars at L/4 th of span & extend -ve bars L/5 th of span.
 9. Do not over lap bottom rods at center and top rods at support.

10. Slab thickness

Project : --
 PROPOSED RESIDENTIAL DUP
 BANGLOWS OF [PHASE - V
 M/s. MODI PROPERTIES AT
 CHERLAPALLY & SHAMIRPE

Sheet Title : --
 PLOT No.: -- TYPE -(B)
 STAIRCASE HEAD ROOM SLA

Drawing no: -- NORTH
 Date : --
 Scale : --
 Dealt By: --
 Chk by: - M. Dattatreya rao.

Architect's: --
Architectural Asso
 # 8-1-383, R . P .ROAD, Sec

Consultant's: --
Kulkarni Consultant's
 Stur. Engineer's & Project Consultant's
 #216, Kubera Tower's, Narayan Guda, Hy