



- GENERAL NOTES**
- USE M25 (1:1:2) GRADE CONCRETE FOR COLUMNS & M20 (1:1.5:3) FOR BEAMS & SLAB
 - USE FE500 GRADE TOR STEEL.
 - PROVIDE CLEAR COVER OF 1.5" FOR COLUMNS , 1" FOR BEAMS & 3/4" FOR SLAB
 - PROVIDE 1" CAMBER AT FREE END FOR CANTILEVER BEAMS & SLABS.
 - IN SLAB EXTEND -VE STEEL UPTO 0.30L FROM FACE OF SUPPORT.
 - DO NOT PROVIDE EXTRA REINFORCEMENT AT SIMPLY SUPPORTS.
 - LAP LENGTH 48 D (D-IS THE DIA OF THE BAR) IN COMPRESSION.
 - LAP LENGTH 52 D (D-IS THE DIA OF THE BAR) IN TENSION.
 - ONLY FIGURED DIMENSIONS SHALL BE FOLLOWED.
 - ALL THE DIMENSIONS ARE IN INCHES & FEET.
 - DO NOT SCALE THE DRAWING.
 - REFER ARCHITECT DRAWING FOR CENTER LINE DIMENSIONS.

REV. NO.	DESCRIPTION	DATE
1		

GOOD FOR CONSTRUCTION

N

Owners & Developers:

Architects & Engineers:

KULKARNI CONSULTANTS

STRUCTURAL ENGINEERS, ARCHITECTS & PROJECT CONSULTANTS

#216, KUMBHAR TOWERS, KUMHAR COLONY, MUMBAI-400002, Maharashtra, India

Phone: +91 22 25454058

E-mail: info@mediproject.com

VISTA HOMES BLOCK - (E)

TYPICAL BEAM SECTION DETAILS(S1)

DATE: 02-05-2019

DRAWN: SMANISH

DESIGNED: SMANISH

CHECKED: KULKARNI

APPROVED: KULKARNI

SCALE: N.T.S.

DWG. NO. KC/WH/SD/E/

REV. NO. 0