



General Notes : --

1. Use M25 (1:1:2) grade for columns & M20 (1:1.5:3) for footings, slab & Bams
2. Use FE415 grade for steel.
3. Provide clear cover of 2" for footings & 1.5" for columns.
4. S.B.C of the Soil is taken as 400kn/m2.
5. Footings are designen for Ground + 2ND floor
6. Provide clear cover of 1"for beams
7. Read horizontal beams from left to right & vertical from bottom to left.
8. crank +ve bars at L/4 th of span & extend -ve bars L/5 th of span.
9. Do not over lap bottom rods at center and top rods at support.
10. Slab thickness

Project : --

PROPOSED RESIDENTIAL DUPL  
BANGLOWS OF [ PHASE- VII  
M/s. MODI PROPERTIES AT  
CHERLAPALLY & SHAMIRPET

Sheet Title : --

WEST FACING PLOT  
PLOT No.: --TYPE -(A)  
STAIRCASE DETAILS

Drawing no: --

Date : -- 18-12-08

Scale : --

Dealt By: - LAXMAN

Chk by: - M. Dattatreya rao.

Architect's: --

**Architectural Asso**

# 8-1-383, R . P .ROAD, Sec

Consultant's: --

**Kulkarni Consultant's**

Stur. Engineer's & Project Consultar

#216, Kubera Tower's, Narayan Guda

NOTE-

1. Refer architects drawing for for thread , riser, & staircase width