



- GENERAL NOTES**
1. USE M25 (1:1.5:2) GRADE CONCRETE FOR COLUMNS & M20 (1:1.5:3) FOR BEAMS & SLAB
  2. USE FE415 GRADE TOR STEEL.
  3. PROVIDE CLEAR COVER OF 1.5" FOR COLUMNS, 1" FOR BEAMS & 3/4" FOR SLAB
  4. PROVIDE 1" CAMBER AT FREE END FOR CANTILEVER BEAMS & SLABS.
  5. IN SLAB EXTEND -VE STEEL UPTO 0.30L FROM FACE OF SUPPORT.
  6. DO NOT PROVIDE EXTRA REINFORCEMENT AT SIMPLY SUPPORTS.
  7. LAP LENGTH 48 D (D - IS THE DIA OF THE BAR) IN COMPRESSION.
  8. LAP LENGTH 52 D (D - IS THE DIA OF THE BAR) IN TENSION.
  9. ONLY FIGURED DIMENSIONS SHALL BE FOLLOWED.
  10. ALL THE DIMENSIONS ARE IN INCHES & FEET.
  11. DO NOT SCALE THE DRAWING.
  12. REFER ARCHITECT DRAWING FOR CENTER LINE DIMENSIONS.



**Architects & Engineers:**  
**KULKARNI CONSULTANTS**  
 STRUCTURAL ENGINEERS, ARCHITECTS & PROJECT CONSULTANTS  
 CONTACT NOS: 0202222893, 09264634724, 07264634723

**Owners & Developers:**  
 5-4-187 /3&4, Soham mansion, II Floor,  
 M.G. Road, Secunderabad-500003,  
 Phone:063555141ines Fax:040-27544058  
 E-mail:info@modiprojects.com

**SCALE:** NTS  
**DATE:** 16-11-16  
**DRAWN:** PAVAN  
**CHECKED:**  
**APPROVED:** KULKARNI

**TITLE:** VISTA HOMES BLOCK - (G)  
 CELLAR BEAM DETAILS

**DMG. NO.** **KC/M/SD/5/8** **SH NCZ**  
**REV. NO.** **0**