	_
	71
33	12
	Ξ
8	t
8	7 (
ı	\Box
	2
	Ξ
	7
١	2
-	_
1	_
- 1	7
- 1	c
- 1	~
1	uality Control Check Repot.
ı	e
1	ರ
- 1	으
-	۲,
ı	
1	
-1	
1	S
- 1	er.
ļ	30
	age
	20e:
	age: A
	age: Aft
	age: After
	age: After
	age: After C
	age: After Col
	age: After Colu
	age: After Colum
	age: After Column
	age: After Column (
	age: After Column C
	age: After Column Cas
	age: After Column Casti
	age: After Column Castin
	age: After Column Casting
	age: After Column Casting (v
	age: After Column Casting (vi
	age: After Column Casting (vill)
	age: After Column Casting (villas

Recommendation: Stop further work. Stop further work. Proceed with furth Proceed with furth	Checked By MD on	Previous stage report no.	Project Manager	Prepared by	Company	Block No.
Recommendation: Stop further work. Submit ATR on QC report to QC team. Proceed only after recheck by QC. Stop further work. Proceed with work after submitting ATR on QC report to QC team. Proceed with further work only after making corrections pointed out in the QC report. ATR n. Proceed with further work. ATR not required.		no.	5		Ni sicu Estates	185.
port to QC team. Proceed ter submitting ATR on ing corrections pointed ired.	MD Sign	33594	Sign	Sign	Project	Column No.
eed only after recheck QC report to QC team I out in the QC report.		Report filed and signed by	5	1.02 mm	Ni laisifotates	02
by QC. ATR not required.	For filling	ed by PM?	Date	Date	Phase	SI. No.
	☐ Yes ☐ No	Yes No	170/41	01 × 0 / 4-1	Ħ	33804

Columns Position Check.

Notes:

- Inspection should be done after casting of columns at each stage and before starting centering works for each slab.
- Prepare Columns Position Check Plan as follows:
- Divide blocks into smaller sub-blocks.
- Show size and orientation of columns. (Tolerance 0.5")
- Show inner inner space between columns. (Tolerance 1") Show diagonals for 20% of bays. (Tolerance 1.5")
- Print an A3 size plan.
- <u>C</u>3.

✓ Yes □ No	dumns Position Check Plan enclosed?
The second with instance assumed the second of the second	
correct dimension with red colour and mention actual dimension post to it	Circle each correct dimension with green colour. Circle each incorrect dimension with red colour and mention achief

- 1. Prepare Slab (or plinth beams) Dimensions Check Plan as follows:
- Show outer dimensions of slab. (Tolerance 2")
- Show length and width of balconies (Tolerance 1")
 Show inner dimensions of ducts and lift well. (Tolerance 1")
- Show location of sunken slab.
- e. Print an A3 size plan.

 Circle each correct dimension with ora

- In the state of	Specified thickness of slab?	Slab Dimensions Check Plan enclosed?	01-1 D:	2. Circle each correct dimension with green colour. Circle each incorrect dimension with red colour and mention a
	Actual thickness of slab?	Yes No	The state of the s	nension with red colour and mention actual din
	57		INCHOLOR GOAL TO IT.	mension payt to it

Quality Control Check Repot. Stage: After Column Casting (villas)

Quality of centering, rod bending and concreting?	Good Avg. Bad
Quality of starters?	Good Avg. Bad
Number and size of honey combs?	☐ High ✓ Medium. ☐ Low
Are the honey combs is slab and columns packed?	☐ Good ☑ Avg. ☐ Bad
Number of beams that are sagging, bulging, caved or deflected in the slab by more than 1"	
Have 6 cubes each for columns and slab casted and numbered for testing?	✓ Yes ☐ No
Remarks: Honey combs factoring not done at Conound flat	stain (ase wrist sta
Bunds for curing made on slab?	
Bund size is less than 100 sft? ✓ Yes □ No	
Drum (200 lts) provided for curing?	9
Gunny bags used for column curing?	
Distance of tap from furthest distance that requires curing. (max permitted 100') 35-0"	
Frequency of curing in number of times a day (enquire from labourers)	
Is the pressure in the curing pipe more than 15' head?	
Quality of infrastructure for curing.	Bad
Remarks:	

Quality Control Check Repot. Stage: After Column Casting (villas)

Columns height, plumb, steel & level marking check.

- Mark v for correct or minor mistake which does not require correction
 Mark X for minor mistake that requires minor correction.
 Mark X for major mistake that requires correction by replacement or re-fixing.
 Mark X X for major mistake that cannot be corrected.
 Tolerance: Plumb 0.25".
 Circle actual height of columns if level differs from specified height by more than 1".

20.	19.	18.	17.	16.	15.	14.	13.	12.	<u> </u>	10.	9.	i,	7.	6.	Ş		. ju	2.	1.			SNO
						20	24	02	Ø	Co	48	38	133	131	Ae	1-1	(A)	73	<u>-</u>			Col No.
						2	2	2	CI	2	C1	0	2	5	5	()	5	C1	2			Col type
						8-4	8-4"	12	14:18	8-1"	1.4-18	8-4"	1.2-8	11 6-18	stain	Stairs	45.19	11-19	n.t. 18		Spec.	Heig
						815"	87511	8764	8-7"	8-2"	8-6"	8-5"	8:4.	816"	Stains	stairs	1418	14-100	8-611		Actual	Height in ft
				2000		4	4	4	4	1	4	<	<	<	\	<	<	<	4	rods	No of	Steel (
				-05		<u>ح</u>	J	ζ,	4,	× (<u> </u>	<u> </u>	۷.	4	\	_	<u></u>	۷,	<	rods	Size of	Steel (v or x)
						<	√	4	_	~	۲,	4	ζ,	۲,	<	<	۷.	<	<			Honeycombs
						<	7	4	<	~	イ	<	<u> </u>	<	<	<	<	<	<		Side 1	Plumb
						く	J.	7	\	\	<	イ	<u> </u>	<	<	<	<	V	۷		Side 2	Plumb (v or x)
☐Yes ☐No	☐ Yes ☐ No	☐Yes ☐No	☐Yes ☐No	☐Yes ☐No	☐ Yes ☐ No	☑Yes □ No	√Yes □No	√ Yes □ No	✓ Yes □ No	✓ Yes □ No	√Yes □ No	Yes No	✓ Yes □ No	Yes No	✓ Yes ☐ No	Yes No	✓ Yes □ No	Yes No	✓ Yes □ No	column?	marked on	Reference level