

Internal memo no. 913-155 – Construction

Date: 23-08-2023

Subject: Removal of cement and paint spots.

Key words: Removal, paint, spots.

1. Most sites are using lappam patti for cleaning tiles, walls, equipment, etc. it is highly inefficient and expensive. Guidelines for cleaning of finished surfaces is give under:
2. For cleaning uneven walls that have patches of cement slurry or paint – use 36 no. Emery paper (coarse).
3. For cleaning of ceramic tiles, vitrified tiles, granite, marble and other finished surfaces – use 400 no. water paper (Emery paper fine). This is to be used with a light hand or else the surface to be cleaned will get scratched.
4. Grime on furniture, equipment, appliances to be removed using CIF Power & Shine Multi-Purpose Cleaner.
5. To clean SS surfaces like sinks, railing, etc., use CIF Abrasive Surface Cleaner Cream with green colour scotch brite scrubber. The same can be used to clean glass windows and doors.
6. For cleaning CP fittings use MYK laticrete Clenza TS tap and shower cleaner. Here again sponge or colour scotch brite scrubber may be used.
7. For cleaning painted surfaces (OBD/emulsion) use surf detergent in warm water with sponge. Use a light hand or else the paint will get scrubbed off.
8. Purchase to maintain stock of these items.
9. Sites to order through SSLLP.

Soham Modi.