

Internal Memo no. 912/161– construction

Date: 19-10-2023

Subject: Guidelines for ordering Adhesive for Tiles/Granite fixing works.

Keywords: Adhesive flooring, wall cladding

1. Adhesive for fixing of tiles and granite for floor, vertical surfaces and below lentils has been standardized.
2. Following material to be used:

| Sl. No. | Description of item                                                                                 | Details of use                                | SKU no.                                                          | Appx. Cost                                                 |
|---------|-----------------------------------------------------------------------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------------------------------------------------|
| 1       | MYK Laticrete 335 Superflex multipurpose floor and wall adhesive - Available in 20 kg & 50 kg bags. | For Wall cladding - both internal & external. | CHEM5982-Chemical-MYK Laticrete-335 Super Flex Adhesive-Misc-Nos | Rs. 956/- per 20 kg bag.<br><br>Rs. 2,006/- per 50 kg bag. |
| 2       | Ultratech tilefixo NT - Available in 25 kg bag.                                                     | – Do -                                        | CHEM3732-Chemical-UltraTech Tilefixo NT-Misc-Nos                 | Rs. 620/- per 25 kg bag.                                   |
| 3       | Adhesive for flooring - MYK Laticrete 305 Grey - Available in 20 kg bag.                            | For Tile & Granite flooring purpose only.     | CHEM6602-Chemical-Tile Adhesive-20kgs-Nos                        | Rs. 266/- per 20 kg bag.                                   |
| 4       | Square Notch Trowel                                                                                 | For maintaining thickness of adhesive         | TOOL9464-Tools-Notched Trowel-Nos                                | Rs. 300/- each.                                            |

Notes:

1. The specified thickness of these adhesives is 6mm (with a tolerance of +/- 2mm) and the coverage area is 35-40 sft per 25kgs bag.
2. Square notch trowel must be used.
3. In case the **plastered surface is uneven** plastering to be corrected before use of adhesive.
4. Plastering to be roughened to receive granite/tile.
5. Purchase to maintain adequate stock.
6. Use of araldite to be eliminated (or minimised). Do not use araldite for making rough surface behind the tile or granite.

Soham Modi