

Subject: Guidelines for ordering Adhesive for Tiles/Granite fixing works.

Keywords: Adhesive flooring, wall cladding

1. Adhesive for fixing of tiles and granite for floor, vertical surfaces and below lentils has been standardized.

2. Following material to be used:

Sl. No.	Description of item	Details of use	SKU no.	Appx. Cost	Initial order Qty, Min. stock Qty, Reorder Qty
1.	MYK Laticrete 345 Superflex Highly Deformable floor and wall adhesive - Available in 20 kg	Use for: External surface wall cladding. Granite cladding below lentil – top member of jambs for fire doors/ windows/ French windows. Cladding of 1200 x 2400 tiles on interior walls.	CHEM4810- Chemical- MYK Laticrete-345 Super Flex Adhesive- Misc- Nos	Rs. 1,800/- per 20 kg bag.	10 – 5 – 5
2.	MYK Laticrete 335 Superflex multipurpose floor and wall adhesive - Available in 20 kg	Use for: Granite jambs (except top member). Internal wall cladding (except large tiles).	CHEM5982- Chemical- MYK Laticrete-335 Super Flex Adhesive- Misc- Nos	Rs. 1,007/- per 20 kg bag.	20 – 10 – 10
3.	MYK Laticrete 325 High Flex Ag Silver floor and wall adhesive - Available in 20 kg	Use for: Bathroom/utility wall and floor tiles – use sparingly as replacement for conventional mortar. Use for flooring over existing tiles or granite.	CHEM5352- Chemical- MYK Laticrete-325 Super Flex Adhesive- Misc- Nos	Rs. 800/- per 20 kg bag.	10 – 5 – 5
4.	Adhesive for flooring - MYK Laticrete 305 Grey - Available in 20 kg bag.	Use for: Flooring of tiles and granite – however, use sparingly only where conventional mortar cannot be used. Use for flooring over VDF or finished concrete.	CHEM6602- Chemical- MYK Laticrete 305- 20kgs- Nos.	Rs. 266/- per 20 kg bag.	50 – 25 – 25

5.	Ultratech tilefixo NT - Available in 25 kg bag.	This is alternate for MYK325 and 305. Use sparingly.	CHEM3732- Chemical- UltraTech Tilefixo NT- Misc-Nos	Rs. 620/- per 25 kg bag.	Nil
6.	Adhesive for flooring and cladding – miscellaneous	Use this SKU for specialty applications or alternate brands in place of MYK	CHEM5170- Chemical- Adhesive wall floor-Misc-Nos	NA	Nil
7.	Square Notch Trowel	For maintaining thickness of adhesive	TOOL9464- Tools- Notched Trowel- Nos	Rs. 300/- each.	10 – 5 – 5

Notes:

1. The thickness of adhesive for wall cladding should be between 4 and 6mm. In case plastered surface is uneven – replaster before using adhesive.
2. For windows and door jambs – check dimensions using MS template. Adhesive cannot exceed 8mm in thickness. Replaster before using adhesive. Jambs for lentil bottoms must be corrected with plastering before using adhesive.
3. Rough plastered surface for wall cladding must have grooves. In case grooves have not been provided - DO NOT HACK WITH CHISSEL – hack with grinding machine + masonry blade in a grid of 200mm.
4. Approximate coverage is about 50 sft per bag.
5. Use of square notch trowel is mandatory. Each site must order 3 trowels before starting work.
6. Purchase to maintain adequate stock of above items.
7. Use of araldite to be eliminated (or minimised). Do not use araldite for making rough surface behind the tile or granite.

Soham Modi