Plot No- D-3, Phase-II, MIDC, Near Pimpleshwar Mandir, Village-Sagaon, Dombivali (East), Maharashtra- 421204 E-Mail: dscpl@dhariaswitchgear.com; sales@dhariaswitchgear.com

TECHNO-COMMERCIAL OFFER

3-Sep-2025 Phone :

Mob : 8121551388

2508-034_R1 Email meenakshi@modiproperties.com

M/s. Modi Properties Pvt. Ltd

Hyderabad | Genome Valley | Telangana | Vizag India.

Kind attention Miss. B.Meenakshi

Subject Your Enquiry dated Thu, Aug 21, For Fire Pump Panel

Referece Your mail dtd: 08.04.23

Dear Sirs

With reference to your subject enquiry, we are please to submit our Techno-Commercial offer as follows: The scope of supply:

Item	Description	Qty
Item # 1	Fire pump panel	3 No

Attached please find our detailed offer comprising of;

Annexure-I : Technical Specification and Make of Components

Annexure-II : Technical / Deviation sheet.

Annexure-III : Bill of Material with overall dimensions and size of Busbar.

Annexure-IV: Price Schedule and Commercial Terms.

We hope you will find our revised offer in line with your requirement and request you to amend the PO accordingly.

Thanking you, Yours faithfully

For Dharia Switchgear & Controls Pvt Ltd

Mahesh Katgeri / Ganesh Ghodmode Sales Team 9833381491 / 8898426619

Annexure-II Technical / Deviation sheet

Sr no	Remark
1	All the switchgears considered are as per GVDC reference drawings/documents.
2	

			Offer No	2508-034_R1
	Annexure-III		Date	03-09-2025
	BILL OF MATERI	AL		
Sr. No.	Description	Model No.	Make	Qty. Req.
	Item # 1	Fire pump panel		
	General			
	GA Enclosure:			
1	GA ENCLOSURE Powder Coating: Enclosure Size: 2000mm (L) x 2275mm (H) x 560mm (D)-Single front; Cable Entry: Top			
	Busbar Material: Alluminium 0.8 Current density Main Bus Position: Bottom)			
	RYB: 1 x 40 x 10			
2	N :1 x 40 x 5			
	E : 1 x 50 x 10 - Al Control BB: 4 x 5 x 5			
Α	MAIN INCOMER			
1	250A TP(N) MCCB IC:			1
1	250A,TP MCCB 50kA,Dsine DN MCCB with Thermal - Magnetic Release DN2-250N Type	CM92006OOP1OG	L&T	1
2	Auxiliary switch DN2, DN3B, DN3, DN4 - 1 C/O	CM998010000	L&T	1
3	Trip Alarm Contact	CM998030000	L&T	1
4	Extended Rotary Handle (ACC dsine DN2 ROM Panel mounting)	CM998300000	L&T	1
5 6	Spreader links (Set of 6) (ACC SPREADER TERMINALS-DN3-400A 3P)	ST980650000	L&T L&T	2
7	Shunt Release, 1 10/240/415V AC,220V DC 160A, DIN Type Isolating Link, Size 2	CM998050000 3NG1000	Siemens	1
8	160A, Fuse Base, Size 2, Suitable for fuselink Type:3NA7 2	3NH3032-0RC	Siemens	1
9	250A/5A, 10VA, Cl-1, Current Transformer for metering	-	Newtek / RECO	3
10	MFM 5010 LED meter Cl 1 with RS485, CTR 2000/5A	WL5010110000	L&T	1
11	Digital Ammeter , Range 0-250A, 3Ph, Flush mounting 96x96mm, (CTR 400A/5A), Accuracy class 1	WL1310100000	L&T	1
12	Digital Voltmeter, Flush mounting 96x96, 3Ph, Range 0-500V, Accuracy class 1	WL1320100000	L&T	1
13	Red, Emergency Stop Push Button	EMNRMH1	L&T	1
14	1NO Contact block for rear mounting for panel mounting	EC1C.	L&T	2
15	Red phase Indicating Lamp (LED),240V AC Yellow phase Indicating Lamp (LED),240V AC	EPLR240A EPLY240A	L&T	1
16 17	Blue phase Indicating Lamp (LED),240V AC	EPLB240A	L&T L&T	1
18	Red (ON) Indicating Lamp (LED),240V AC	EPLR240A	L&T	1
19	Green (OFF) Indicating Lamp (LED),240V AC	EPLG240A	L&T	1
20	Amber (TRIP) Indicating Lamp (LED),240V AC	EPLA240A	L&T	1
21	6A Fuses Link, 415V AC, type : HF, Size : 14 X 51, 80kA.	SF90146	L&T	5
22	32A Fuse Base, 415V AC, type: HCO 32, suitable for Fuse type:HF.	SK91314	L&T	5
23	20A,Neutral links	-	Cands	3
2	SP Htr and Thermostat			3
1	30 - 85 Degree Thermostate	THERMOSTATE	APT	3
2	100Watts, 220-240V AC, 1Ph, Panel Space Heater	HEATER	APT	3
3	6A DP,MCB, 10kA 5A 3Pin socket	BB20060C	L&T	3
5	5 Watt LED		Anchor Reputed	3
В	OUT GOING FEEDERS:			
3	45KW STAR-DELTA STARTER (Main Pump-1 &2):			2
1	160A, 50KA, TP MCCB with Dsine DN MCCBs for Motor back-up Protection DN1- 160M Typr	CM9034500MO	L&T	2
2	Extended Door Mounted Rotary Operator. (DN1)	CM980410000	L&T	2
3 4	Auxiliary Switch (AUX) (1 C/O) (DN1) Spreader Links - Set of 6 (DN1)	CM97886OOOO EM90609OOOO	L&T L&T	2
	95A, TP, AC3 Power Contactor, Coil : 240V AC, MO 95, Fr 3.	CS94577 BOOO	L&T	4
	1 NO + 1 NC Front ADD On Aux. block for MO 09-110.	CS94592 0000	L&T	4

0	ZOA TD AC2 Dower Contactor Coil + 240V/AC MAC 70 Fr 2	CS04574BOOO	L&T	2
9	70A, TP, AC3 Power Contactor, Coil : 240V AC, MO 70, Fr 2. 2NO+2NC Front ADD On contact block for MO 09-110.	CS94574BOOO CS94596 OOOO	L&T	2
10	Thermal OLR (37-49A) (Separate Mounting) Type RT0-3 (Directly operated)	CS96304OOGO	L&T	2
11	Reset Cord for Thermal OLR-650 mm (For RTO Relay)	CS909420000	L&T	2
12	10A, Auto/Manual Selector Switch, 2 Pole, 2 Way, with NO OFF, 250V AC/DC.	2S26B	Kaycee	2
12	Tow, Auto/Manual Selector Switch, 2 Fole, 2 Way, with NO Off, 250V AC/DC.	23200	·	
13	Red, normal opaque actuator with holder for contact block modular push button	EMNRFD1	L&T	2
14	Contact Block 1 NC for Push Button	EC2C	L&T	2
15	Green, normal opaque actuator with holder for contact block modular push button	EMNGFD1	L&T	2
16	Contact Block 1 NC for Push Button	EC2C	L&T	2
17	Star delta timer, Micon 175 SD Timer 240VAC/24VAC/DC, 60ms	12SDT0	L&T	2
18	Red (ON) Indicating Lamp (LED),240V AC	EPLR240A	L&T	2
19	Green (OFF) Indicating Lamp (LED),240V AC	EPLG240A	L&T	2
20	Amber (TRIP) Indicating Lamp (LED),240V AC	EPLA240A	L&T	2
21	Blue (PRESSURE OK) Indicating Lamp (LED),240V AC	EPLB240A	L&T	2
22	10A, Aux. Contactor, 2NO+2NC, AC 240V Coil, (MO 0AC) (2NO+2NC) Contactor 240 V 50/60 Hz)	CS91625BOOO	L&T	4
23	6A Fuses Link, 415V AC, type: HG, Size: 14 X 51, 80kA.	SF90146	L&T	2
24	32A Fuse Base, 415V AC, type : HCO , suitable for Fuse type:HF.	SK91314	L&T	2
25	20A,Neutral links	-	Cands	4
26	Thermister Relay,230V AC Coil vtg. with1C/O contact for sensing motor winding temperature through PTC Thermistors. Winding overheating sensor short, sensor open faults, suitable for single, triple for 6/9/12 PTCs	S2-WTR1	Minilec	2
27	24V DC, 5A, DPDT Plug-in-Relay with 2C/O Contact.	MY2N DC24 BY OMZ	Omron	8
28	Socket for above Plug-in-Relay, DIN Rail mouting.	PYF08A-E NBY OMZ	Omron	8
29	6A DP,MCB, 10kA	BB20060C	L&T	2
4	5.5KW DOL STARTER (Jockey Pump-1 &2):			2
1	13A, 3P, MPCB, 50kA, 415V AC, 50Hz. for Motor Application (Type MOG-H1)	ST419140000	L&T	2
2	Extended Rotary Handle (Type MOG)	ST419550000	L&T	2
3	Auxiliary Contact Left Side Mtg 1NO+1NC (Type MOG)	ST419450000	L&T	2
4	25A, TP, AC3 Power Contactor, Coil : 240V AC, MO 25, Fr 1.	CS94567BOOO	L&T	2
5 6	2NO+2NC Auxiliary Contact Blocks for snapping onto the front For MO 9-110 1NO+1NC Auxiliary Contact Blocks for snapping onto the first left side mounting For MO 9-	CS945960000 CS945920000	L&T L&T	2
7	110 10A, Aux. Contactor, 2NO+2NC, AC 240V Coil, (MO 0AC) (2NO+2NC) Contactor 240 V	CS91625BOOO	L&T	2
	50/60 Hz)			
8	Thermal OLR (9-45) Type REO 1.1 Direct Mounting on MO 9-45	CS9041800G0	L&T	2
9	Reset Cord for Thermal OLR-650 mm	CS904250000	L&T	2
10	10A, Auto/Manual Selector Switch, 2 Pole, 2 Way, with NO OFF, 250V AC/DC.	2S26B	Kaycee	2
11	Red, normal opaque actuator with holder for contact block modular push button	EMNRFD1	L&T	2
12	Contact Block 1 NC for Push Button	EC2C	L&T	2
13	Green, normal opaque actuator with holder for contact block modular push button	EMNGFD1	L&T	2
14	1NO Contact block for rear mounting for panel mounting	EC1C	L&T	2
15	Red (ON) Indicating Lamp (LED),240V AC	EPLR240A	L&T	2
16	Green (OFF) Indicating Lamp (LED),240V AC	EPLG240A	L&T	2
17	Amber (TRIP) Indicating Lamp (LED),240V AC	EPLA240A	L&T	2
18	6A Fuses Link, 415V AC, type : HG, Size : 14 X 51, 80kA.	SF90146	L&T	2
19	32A Fuse Base, 415V AC, type: HCO, suitable for Fuse type:HF.	SK91314	L&T	2
20	20A,Neutral links	-	Cands	2
21	24V DC, 5A, DPDT Plug-in-Relay with 2C/O Contact.	MY2N DC24 BY OMZ	Omron	12
22	Socket for above Plug-in-Relay, DIN Rail mouting.	PYF08A-E NBY OMZ	Omron	12
				1
5	32A TPN MCCB OUTGOING FEEDER:	D707000011110110000	1.0-	
1	32A TPN MCCB OUTGOING FEEDER: 32A,TP MCCB 50kA, with Thermal Magnetic Release (MCCB dsine DZ1-160N)	DZ2T0032NXC1A0000	L&T	1
1 2	32A,TP MCCB 50kA, with Thermal Magnetic Release (MCCB dsine DZ1-160N) Extended Rotary Handle (DZ1)	DZ2T0032NXC1AOOOO EM90209OOOO	L&T	1
1	32A,TP MCCB 50kA, with Thermal Magnetic Release (MCCB dsine DZ1-160N)			

6	63A TPN MCCB OUTGOING FEEDER:			1
1	63A,TP MCCB 50kA, with Thermal Magnetic Release (MCCB dsine DZ1-160N)	DZ2T0063NXD1AOOOO	L&T	1
2	Extended Rotary Handle (DZ1)	EM902090000	L&T	1
3	Isolating Neutral link	-	Reputed	1

Annexure-IV Price Schedule and Commo	ercial Terms.	
Offer No 2508-034_R1	Date	3-Sep-25

Price (F.O.R. Site)	Qty	Unit Price (Rs.)	Total Price (Rs.)
Item # 1 Fire pump panel	1 No	3,15,000 /-	9,45,000 /-
		Grand Total	9,45,000 /-

FREIGHT & INSURANCE & SITE SERVICES

Our prices are EX works, Site services will be per manday charges.

PACKING

Included in the offer

GST

This will be charged extra @ 18%.

INSPECTION / TESTING

Switchboards will be offered for inspection within 6 weeks from the date of receipt of manufacturing clearance.

Drawing will be submitted by us within 1 week from the date of receipt of your Purchase Order

The delivery indicated by us is "Subject to force majeure conditions".

PAYMENT

30% of the value along with the Purchase Order against and balance 70% with applicable taxes and duties against Proforma invoice.

GUARANTEE

Our equipment are guaranteed for 12 months from date of dispatch.

VALIDITY

This offer is valid for 15 days since this day and thereafter subject to confirmation from our side.

Thanking you

Yours faithfully

For Dharia Switchgear & Controls Pvt Ltd

Mahesh Katgeri / Ganesh Ghodmode Sales Team