



# DHARIA SWITCHGEAR & CONTROLS PVT. LTD.

Plot No- D-3, Phase-II , MIDC, Near Pimpleshwar Mandir, Village-Sagaon, Dombivali (East), Maharashtra- 421204  
E-Mail : [dscpl@dhariaswitchgear.com](mailto:dscpl@dhariaswitchgear.com); [sales@dhariaswitchgear.com](mailto:sales@dhariaswitchgear.com)

## TECHNO-COMMERCIAL OFFER

5-Jan-2026

Phone :

2508-035\_R2

Mob : 8121551388

Email [meenakshi@modiproperties.com](mailto:meenakshi@modiproperties.com)

**M/s. G.V. Innopolis Research Centre. Pvt. Ltd.,**  
GENOME VALLEY,  
Life Sciences Park, Hyderabad  
India.

Kind attention **Miss. B.Meenakshi**

Subject Your Enquiry -

Referece Your mail dtd:-

Dear Sirs

With reference to your subject enquiry, we are please to submit our Techno-Commercial offer as follows :-  
The scope of supply :

Item	Description	Qty
Item # 1	2000A ACB OG Extension	1 No
Item # 2	SUB PCC-3A 2000A IC	1 No
Item # 3	SUB PCC-3B 2000A IC	1 No

Attached please find our detailed offer comprising of ;

- Annexure-I : Technical Specification and Make of Components
- Annexure-II : Technical / Deviation sheet.
- Annexure-III : Bill of Material with overall dimensions and size of Busbar.
- Annexure-IV : Price Schedule and Commercial Terms.

We hope you will find our revised offer in line with your requirement and request you to amend the PO accordingly.

Thanking you,

Yours faithfully

**For Dharia Switchgear & Controls Pvt Ltd**

Ganesh Ghodmode  
Sales Team  
9833381491 / 8898426619

**Annexure-II**  
**Technical / Deviation sheet**

---

<b>Sr no</b>	<b>Remark</b>
1	All the switchgears considered are as per GVRC reference drawings/documents.
2	

		Offer No	2508-035_R2
		Date	05-01-2026

**Annexure-III**

**BILL OF MATERIAL**

Sr. No.	Description	Model No.	Make	Qty. Req.
	<b>Item # 1</b>	<b>2000A ACB OG Extension</b>		
	<b>General</b>			
1	<b>GA Enclosure:</b> GA ENCLOSURE Powder Coating: Enclosure Size: 850mm (L) x 2055mm (H) x 1680mm (D)-Single front; Cable Entry: TOP			
	<b>Busbar Material: Alluminium 0.8 Current density Main Bus Position: Bottom)</b>			
2	RYB : 2 x 2 x 160 x 10 N : 3 x 100 x 10 E : 1 x 50 x 10 -Al Control BB: 4 x 5 x 5			
<b>A MAIN INCOMER</b>				
1	<b>2000A TP(N) ACB OG:</b>			<b>1</b>
1	2000A Ics=Icw=Icu=50kA for 1 Sec, 3P MDO ACB(U-POWER/OMEGA), LSING release with microprocessor based, O/C, S/C & E/F protection, MTX1G SHUNT TRIP - 240 V AC WITH 4NO+4NC CONTACTS WITH ALL STANDARD ACCESSORIES External N-CT Fr1 2000-2500A;OMEGA	UW120NXD01900	L&K	1
2	25A Breaker Control Switch ODS type for 250V AC/DC, with pistol grip handle, spring return to neutral, with 2NO at CLOSE & 2NO at TRIP	BCA02 P006K144/S/N	Kaycee	1
3	16A AC/DC Switch Rotary, 1 Pole,2 Way,NO OFF,250V AC/DC,2 Position,90 Deg,1-AUTO,2-MANUAL	RP113	Kaycee	1
4	2000/5A, 10 VA, Accuracy class 1, Metering Current Transformer	-	Newtek/Reco	3
5	MFM 5010 LED meter CI 1 with RS485, CTR 2000/5A	WL5010110000	L&K	3
6	Digital Ammeter , Range 0-2000A, 3Ph, Flush mounting 96x96mm, (CTR 2000A/5A), Accuracy class 1	WL1310100000	L&K	1
7	Digital Voltmeter, Flush mounting 96x96, 3Ph, Range 0-500V, Accuracy class 1	WL1320100000	L&K	1
8	10A, Aux. Contactor, 4NO, AC 240V Coil, (MO0 40E) 50/60 Hz	CS91623B000	L&K	1
9	10A, Aux. Contactor, 3NO+1NC, AC 240V Coil, (MO0 31E) 50/60 Hz	CS91624B000	L&K	2
10	Red, Emergency Stop Push Button	EMNRMH1	L&K	2
11	1NO Contact block for rear mounting for panel mounting	EC1C	L&K	1
12	1NC Contact block for rear mounting for panel mounting	EC2C	L&K	2
13	White, normal opaque actuator with holder for contact block modular push button	EMNWFD1	L&K	1
14	Red (ON) Indicating Lamp (LED),240V AC	EPLR240A	L&K	1
15	Green (OFF) Indicating Lamp (LED),240V AC	EPLG240A	L&K	1
16	Amber (TRIP) Indicating Lamp (LED),240V AC	EPLA240A	L&K	1
17	White (TRIP CKT. HEALTHY) Indicating Lamp (LED),240V AC	EPLW240A	L&K	1
18	Red (Sevice Position) Indicating Lamp (LED),240V AC	EPLR240A	L&K	1
19	Yellow (Test Position) Indicating Lamp (LED),240V AC	EPLY240A	L&K	1
20	6A, 2P, 10kA, C Curve MCB	BB20060C	L&K	1
21	6A Fuses Link, 415V AC, type : HF, Size : 14 X 51, 80kA.	SF90146	L&K	4
22	32A Fuse Base, 415V AC, type : HCO 32, suitable for Fuse type:HF.	SK91314	L&K	3
23	20A,Neutral links	-	Cands	3

	<b>Item # 2</b>	<b>SUB PCC-3A 2000A IC</b>		
	<b>General</b>			
1	<b>GA Enclosure:</b> GA ENCLOSURE Powder Coating: Enclosure Size: 3690mm (L) x 2055mm (H) x 1120/560mm (D)-Single front			
	<b>Busbar Material: Alluminium 0.8 Current density</b>			
2	RYB : 2 x 140 x 10 N : 1 x 100 x 10 E : 1 x 50 x 10 -Al Control BB: 6 x 5 x 5			

<b>A MAIN INCOMERS:</b>				
<b>1</b>	<b>2000A 4P ACB I/C (With cable entry):</b>			<b>1</b>
1	2000A Ics=Icw=Icu=50kA for 1 Sec, 4P EDO ACB (UPOWER/OMEGA) Frame Size 1, with 240V AC Spring Charge Motor, LSING release with microprocessor based, O/C, S/C & E/F protection, MTX1G with all standard accessories such as closing coil 240VAC, Shunt Trip 240VAC, Micro Switches for Shunt Release, Under Voltage, Common Fault Indication, 4NO+4NC Aux contacts, Smart-racking, shutter, Safety shutter assembly, Racking Handle, Door sealing frame, Pad-locking arrangement for ON/OFF button, Rating Error Preventer, Arc shield, ) For ratings upto 2000A, one side vertical terminal adaptors (Bottom) for Frame 1, etc...	UW120NFD12900	L&K	1
2	U/V RELEASE - 415V AC	CL90818D000	L&K	1
3	POSITION SIGNAL SWITCH FOR WITHDRAWABLE BREAKER	CL95826O000	L&K	1
4	MICROSWITCH FOR SPRING CHARGING	ST42672O000	L&K	1
5	Frame-1250-2000A N/S/H (Top Horizontal & Bottom Vertical)	CL60963O000	L&K	1
6	Door Interlock	CL90978O000	L&K	1
7	25A Breaker Control Switch ODS type for 250V AC/DC, with pistol grip handle, spring return to neutral, with 2NO at CLOSE & 2NO at TRIP	BCA02 P006K144/S/N	Kaycee	1
8	16A AC/DC Switch Rotary, 1 Pole,2 Way,NO OFF,250V AC/DC,2 Position,90 Deg,1-AUTO,2-MANUAL	RP113A/TB3	Kaycee	1
9	2000/5A, 10 VA, Accuracy class 1, Metering Current Transformer	-	Newtek/Reco	3
10	MFM 5000 LED meter CI 0.5S with Ethernet, CTR-2000A/5A, Aux. supply 240V AC.	WL500032O000	L&K	1
11	Digital Ammeter with in-built Selector Switch, Range 0-2000A, 3Ph, Flush mounting 96x96mm, (CTR 2000A/5A), Accuracy class 1, Aux. supply 240V AC.	WL131010O000	L&K	1
12	Digital Voltmeter with in-built Selector Switch, Flush mounting 96x96, 3Ph, Range 0-500V, Accuracy class 1, Aux. supply 240V AC.	WL132010O000	L&K	1
13	Electronic timer, On-delay with 1C/O contact, 5 – 100 sec, 24/200-240AC, 24DC	3RP1513-1AP308K	Siemens	1
14	12A, Power contactor, 1NO, AC 240V Coil (MNX 12)	CS94108B000	L&K	1
15	1NO+1NC MNX / MCX Front Mounting Add-on aux. Contact Block	CS94118O000	L&K	1
16	10A, Aux. Contactor, 2NO+2NC, AC 240V Coil, (MO0 22E) 50/60 Hz	CS91625B000	L&K	4
17	10A, Aux. Contactor, 4NO, AC 240V Coil, (MO0 40E) 50/60 Hz	CS91623B000	L&K	2
18	Red, Emergency Stop Push Button (Mushroom Head 'Push - Turn Function')	EMNRMH1	L&K	1
19	White, normal opaque actuator with holder for contact block modular push button	EMNWF1	L&K	1
20	1NO Contact block for rear mounting for panel mounting	EC1C	L&K	2
21	1NC Contact block for rear mounting for panel mounting	EC2C	L&K	1
22	Red phase Indicating Lamp (LED),240V AC	EPLR240A	L&K	1
23	Yellow phase Indicating Lamp (LED),240V AC	EPLY240A	L&K	1
24	Blue phase Indicating Lamp (LED),240V AC	EPLB240A	L&K	1
25	Red (ON) Indicating Lamp (LED),240V AC	EPLR240A	L&K	1
26	Green (OFF) Indicating Lamp (LED),240V AC	EPLG240A	L&K	1
27	Amber (TRIP) Indicating Lamp (LED),240V AC	EPLA240A	L&K	1
28	White (TRIP CKT. HEALTHY) Indicating Lamp (LED),240V AC	EPLW240A	L&K	1
29	Blue (Spring Charged) Indicating Lamp (LED),240V AC	EPLB240A	L&K	1
30	Red (Sevice Position) Indicating Lamp (LED),240V AC	EPLR240A	L&K	1
31	Yellow (Test Position) Indicating Lamp (LED),240V AC	EPLY240A	L&K	1
32	16A, 4P, 10kA, C Curve MCB	BB40160C	L&K	1
33	6A, 2P, 10kA, C Curve MCB	BB20060C	L&K	5
34	6A Fuses Link, 415V AC, type : HF, Size : 14 X 51, 80kA	SF90146	L&K	9
35	32A Fuse Base, 415V AC, type : HCO 32, suitable for Fuse type:HF	SK91314	L&K	9
36	20A,Neutral links	-	Cands	3
37	Class B SPD for power line protection (L-N), Main LT Panel.	MCD 50-B-OS-320	OBO	3
38	Class B SPD for power line protection (N-PE), Main LT Panel.	MCD 125-B-NPE	OBO	1
39	125A Fuse Size 00 for HB 160 Fuse base	SF94030	L&K	3
40	HB 160 Fuse bases suitable for Cylindrical / DIN fuse-links	SK90405	L&K	3
<b>3</b>	<b>SP Htr and Thermostat</b>			<b>5</b>
1	30 - 85 Degree Thermostate	THERMOSTATE	APT	5
2	200Watts, 220-240V AC, 1Ph, Panel Space Heater	HEATER	APT	2
3	100Watts, 220-240V AC, 1Ph, Panel Space Heater	HEATER	APT	3
4	6A DP,MCB, 10kA	BB20060C	L&K	10
5	5A 3Pin socket		Anchor	5

6	5 Watt LED with holder		Reputed	5
<b>B Out Going Feeders:</b>				
<b>1</b>	<b>2000A TP(N) ACB OG:</b>			<b>1</b>
1	2000A Ics=Icw=Icu=50kA for 1 Sec, 3P MDO ACB(U-POWER/OMEGA), LSING release with microprocessor based, O/C, S/C & E/F protection, MTX1G SHUNT TRIP - 240 V AC WITH 4NO+4NC CONTACTS WITH ALL STANDARD ACCESSORIES External N-CT Fr1 2000-2500A/OMEGA	UW120NXD01900	L&K	1
2	Door Interlock	CL909780000	L&K	1
3	MICROSWITCH FOR SPRING CHARGING	ST426720000	L&K	1
4	16A AC/DC Switch Rotary, 1 Pole,2 Way,NO OFF,250V AC/DC,2 Position,90 Deg,1-AUTO,2-MANUAL	RP113A/TB3	Kaycee	1
5	25A Breaker Control Switch ODS type for 250V AC/DC, with pistol grip handle, spring return to neutral, with 2NO at CLOSE & 2NO at TRIP	BCA02 P006K144/S/N	Kaycee	1
6	2000/5A, 10 VA, Accuracy class 1, Metering Current Transformer	-	Newtek/Reco	3
7	MFM 5010 LED meter CI 1 with RS485, CTR 2000/5A	WL5010110000	L&K	1
8	Digital Ammeter , Range 0-2000A, 3Ph, Flush mounting 96x96mm, (CTR 2000A/5A), Accuracy class 1	WL1310100000	L&K	1
9	Digital Voltmeter, Flush mounting 96x96, 3Ph, Range 0-500V, Accuracy class 1	WL1320100000	L&K	1
10	10A, Aux. Contactor, 4NO, AC 240V Coil, (MO0 40E) 50/60 Hz	CS91623B000	L&K	2
11	10A, Aux. Contactor, 3NO+1NC, AC 240V Coil, (MO0 31E) 50/60 Hz	CS91624B000	L&K	2
12	Red, Emergency Stop Push Button	EMNRMH1	L&K	1
13	1NO Contact block for rear mounting for panel mounting	EC1C	L&K	2
14	1NC Contact block for rear mounting for panel mounting	EC2C	L&K	1
15	White, normal opaque actuator with holder for contact block modular push button	EMNWFD1	L&K	1
16	Red (ON) Indicating Lamp (LED),240V AC	EPLR240A	L&K	1
17	Green (OFF) Indicating Lamp (LED),240V AC	EPLG240A	L&K	1
18	Amber (TRIP) Indicating Lamp (LED),240V AC	EPLA240A	L&K	1
19	White (TRIP CKT. HEALTHY) Indicating Lamp (LED),240V AC	EPLW240A	L&K	1
20	Red (Sevice Position) Indicating Lamp (LED),240V AC	EPLR240A	L&K	1
21	Yellow (Test Position) Indicating Lamp (LED),240V AC	EPLY240A	L&K	1
22	6A, 2P, 10kA, C Curve MCB	BB20060C	L&K	4
23	6A Fuses Link, 415V AC, type : HF, Size : 14 X 51, 80kA.	SF90146	L&K	3
24	32A Fuse Base, 415V AC, type : HCO 32, suitable for Fuse type:HF.	SK91314	L&K	3
25	20A,Neutral links	-	Cands	1
<b>5</b>	<b>630A TP(N) MCCB OG:</b>			<b>6</b>
1	630A,TP MCCB 50kA, With Microprocessor Release MTX2.0 (MCCB dsine DN3-630N 630A),	CM930060000AG	L&K	6
2	Auxiliary switch 1 C/O+1 C/O Trip aux contact (ACC DN3 Right)	CM998040000	L&K	6
3	Extended Rotary Handle (ACC dsine DN3 ROM Panel mounting)	CM998610000	L&K	6
4	Spreader links (Set of 6) (ACC SPREADER TERMINALS-DN3-630A 3P)	ST980540000	L&K	6
5	400A, DIN Type Isolating Link, Size 2	3NG1300	Siemens	6
6	400A, Fuse Base, Size 2, Suitable for fuselink Type:3NA7 2	3NH3330-0RC	Siemens	6
7	630A/5A, 10VA, CI-1, Current Transformer for metering	-	Newtek/Reco	18
8	MFM 4040 Dual Source LCD meter CI 1 with RS485, CTR 630/5A	WC4040110000	L&K	6
9	Red (ON) Indicating Lamp (LED),240V AC	EPLR240A	L&K	6
10	Green (OFF) Indicating Lamp (LED),240V AC	EPLG240A	L&K	6
11	Amber (TRIP) Indicating Lamp (LED),240V AC	EPLA240A	L&K	6
12	6A, 2P, 10kA, C Curve MCB	BB20060C	L&K	6
13	6A Fuses Link, 415V AC, type : HF, Size : 14 X 51, 80kA.	SF90146	L&K	18
14	32A Fuse Base, 415V AC, type : HCO 32, suitable for Fuse type:HF.	SK91314	L&K	18
15	20A,Neutral links	-	Cands	6
<b>Item # 3</b>		<b>SUB PCC-3B 2000A IC</b>		
<b>1</b>	<b>General</b>			
	<b>GA Enclosure:</b>			
	GA ENCLOSURE Powder Coating:			
	Enclosure Size: 3370mm (L) x 2055mm (H) x 1120/560mm (D)-Single front			
<b>2</b>	<b>Busbar Material: Alluminium 0.8 Current density</b>			
	RYB : 2 x 140 x 10			
	N : 1 x 100 x 10			
	E : 1 x 50 x 10 -Al			
	Control BB: 6 x 5 x 5			

<b>A MAIN INCOMERS:</b>				
<b>1</b>	<b>2000A 4P ACB 1/C (With cable entry):</b>			<b>1</b>
1	2000A Ics=Icw=Icu=50kA for 1 Sec, 4P EDO ACB (UPOWER/OMEGA) Frame Size 1, with 240V AC Spring Charge Motor, LSING release with microprocessor based, O/C, S/C & E/F protection, MTX1G with all standard accessories such as closing coil 240VAC, Shunt Trip 240VAC, Micro Switches for Shunt Release, Under Voltage, Common Fault Indication, 4NO+4NC Aux contacts, Smart-racking, shutter, Safety shutter assembly, Racking Handle, Door sealing frame, Pad-locking arrangement for ON/OFF button, Rating Error Preventer, Arc shield, ) For ratings upto 2000A, one side vertical terminal adaptors (Bottom) for Frame 1, etc...	UW120NFD12900	L&K	1
2	U/V RELEASE - 415V AC	CL90818DOOO	L&K	1
3	POSITION SIGNAL SWITCH FOR WITHDRAWABLE BREAKER	CL95826O000	L&K	1
4	MICROSWITCH FOR SPRING CHARGING	ST42672O000	L&K	1
5	Frame-1250-2000A N/S/H (Top Horizontal & Bottom Vertical)	CL60963O000	L&K	1
6	Door Interlock	CL90978O000	L&K	1
7	25A Breaker Control Switch ODS type for 250V AC/DC, with pistol grip handle, spring return to neutral, with 2NO at CLOSE & 2NO at TRIP	BCA02 P006K144/S/N	Kaycee	1
8	16A AC/DC Switch Rotary, 1 Pole,2 Way,NO OFF,250V AC/DC,2 Position,90 Deg,1-AUTO,2-MANUAL	RP113A/TB3	Kaycee	1
9	2000/5A, 10 VA, Accuracy class 1, Metering Current Transformer	-	Newtek/Reco	3
10	MFM 5000 LED meter CI 0.5S with Ethernet, CTR-2000A/5A, Aux. supply 240V AC.	WL500032O000	L&K	1
11	Digital Ammeter with in-built Selector Switch, Range 0-2000A, 3Ph, Flush mounting 96x96mm, (CTR 2000A/5A), Accuracy class 1, Aux. supply 240V AC.	WL131010O000	L&K	1
12	Digital Voltmeter with in-built Selector Switch, Flush mounting 96x96, 3Ph, Range 0-500V, Accuracy class 1, Aux. supply 240V AC.	WL132010O000	L&K	1
13	Electronic timer, On-delay with 1C/O contact, 5 – 100 sec, 24/200-240AC, 24DC	3RP1513-1AP308K	Siemens	1
14	12A, Power contactor, 1NO, AC 240V Coil (MNX 12)	CS94108B000	L&K	1
15	1NO+1NC MNX / MCX Front Mounting Add-on aux. Contact Block	CS94118O000	L&K	1
16	10A, Aux. Contactor, 2NO+2NC, AC 240V Coil, (MOO 22E) 50/60 Hz	CS91625B000	L&K	4
17	10A, Aux. Contactor, 4NO, AC 240V Coil, (MOO 40E) 50/60 Hz	CS91623B000	L&K	2
18	Red, Emergency Stop Push Button (Mushroom Head 'Push - Turn Function')	EMNRMH1	L&K	1
19	White, normal opaque actuator with holder for contact block modular push button	EMNWFD1	L&K	1
20	1NO Contact block for rear mounting for panel mounting	EC1C	L&K	2
21	1NC Contact block for rear mounting for panel mounting	EC2C	L&K	1
22	Red phase Indicating Lamp (LED),240V AC	EPLR240A	L&K	1
23	Yellow phase Indicating Lamp (LED),240V AC	EPLY240A	L&K	1
24	Blue phase Indicating Lamp (LED),240V AC	EPLB240A	L&K	1
25	Red (ON) Indicating Lamp (LED),240V AC	EPLR240A	L&K	1
26	Green (OFF) Indicating Lamp (LED),240V AC	EPLG240A	L&K	1
27	Amber (TRIP) Indicating Lamp (LED),240V AC	EPLA240A	L&K	1
28	White (TRIP CKT. HEALTHY) Indicating Lamp (LED),240V AC	EPLW240A	L&K	1
29	Blue (Spring Charged) Indicating Lamp (LED),240V AC	EPLB240A	L&K	1
30	Red (Sevice Position) Indicating Lamp (LED),240V AC	EPLR240A	L&K	1
31	Yellow (Test Position) Indicating Lamp (LED),240V AC	EPLY240A	L&K	1
32	16A, 4P, 10kA, C Curve MCB	BB40160C	L&K	1
33	6A, 2P, 10kA, C Curve MCB	BB20060C	L&K	5
34	6A Fuses Link, 415V AC, type : HF, Size : 14 X 51, 80kA	SF90146	L&K	9
35	32A Fuse Base, 415V AC, type : HCO 32, suitable for Fuse type:HF	SK91314	L&K	9
36	20A,Neutral links	-	Cands	3
37	Class B SPD for power line protection (L-N), Main LT Panel.	MCD 50-B-OS-320	OBO	3
38	Class B SPD for power line protection (N-PE), Main LT Panel.	MCD 125-B-NPE	OBO	1
39	125A Fuse Size 00 for HB 160 Fuse base	SF94030	L&K	3
40	HB 160 Fuse bases suitable for Cylindrical / DIN fuse-links	SK90405	L&K	3
<b>3</b>	<b>SP Htr and Thermostat</b>			<b>5</b>
1	30 - 85 Degree Thermostate	THERMOSTATE	APT	5
2	200Watts, 220-240V AC, 1Ph, Panel Space Heater	HEATER	APT	1
3	100Watts, 220-240V AC, 1Ph, Panel Space Heater	HEATER	APT	4
4	6A DP,MCB, 10kA	BB20060C	L&K	10

5	5A 3Pin socket		Anchor	5
6	5 Watt LED with holder		Reputed	5
<b>B Out Going Feeders:</b>				
<b>2</b>	<b>630A TP(N) MCCB OG:</b>			<b>8</b>
1	630A,TP MCCB 50kA, With Microprocessor Release <b>MTX2.0</b> (MCCB dsine DN3-630N 630A),	CM930060000AG	L&K	8
2	Auxiliary switch 1 C/O+1 C/O Trip aux contact (ACC DN3 Right)	CM998040000	L&K	8
3	Extended Rotary Handle (ACC dsine DN3 ROM Panel mounting)	CM998610000	L&K	8
4	Spreader links (Set of 6) (ACC SPREADER TERMINALS-DN3-630A 3P)	ST980540000	L&K	8
5	400A, DIN Type Isolating Link, Size 2	3NG1300	Siemens	8
6	400A, Fuse Base, Size 2, Suitable for fuselink Type:3NA7 2	3NH3330-ORC	Siemens	8
7	630A/5A, 10VA, CI-1, Current Transformer for metering	-	Newtek/Reco	24
8	MFM 4040 Dual Source LCD meter CI 1 with RS485, CTR 630/5A	WC4040110000	L&K	8
9	Red (ON) Indicating Lamp (LED),240V AC	EPLR240A	L&K	8
10	Green (OFF) Indicating Lamp (LED),240V AC	EPLG240A	L&K	8
11	Amber (TRIP) Indicating Lamp (LED),240V AC	EPLA240A	L&K	8
12	6A, 2P, 10kA, C Curve MCB	BB20060C	L&K	8
13	6A Fuses Link, 415V AC, type : HF, Size : 14 X 51, 80kA.	SF90146	L&K	24
14	32A Fuse Base, 415V AC, type : HCO 32, suitable for Fuse type:HF.	SK91314	L&K	24
15	20A,Neutral links	-	Cands	8

<b>Annexure-IV</b>			
<b>Price Schedule and Commercial Terms.</b>			
<b>Offer No</b>	<b>2508-035_R2</b>	<b>Date</b>	<b>5-Jan-26</b>

<b>Price (F.O.R. Site)</b>	<b>Qty</b>	<b>Unit Price (Rs.)</b>	<b>Total Price (Rs.)</b>
Item # 1 2000A ACB OG Extension	1 No	4,46,000 /-	4,46,000 /-
Item # 2 SUB PCC-3A 2000A IC	1 No	14,70,000 /-	14,70,000 /-
Item # 3 SUB PCC-3B 2000A IC	1 No	13,70,200 /-	13,70,200 /-
<b>Grand Total ...</b>			<b>32,86,200 /-</b>

**FREIGHT & INSURANCE & SITE SERVICES**

Included in the offer

**PACKING**

Included in the offer

**GST**

This will be charged extra @ 18%.

**INSPECTION / TESTING**

Switchboard will be offered for inspection within 10 weeks from the date of receipt of manufacturing clearance.

Drawings will be submitted by us within 1 week from the date of receipt of your Purchase Order

The delivery indicated by us is "**Subject to force majeure conditions**".

**PAYMENT**

30% of the value along with the Purchase Order against and balance 70% with applicable taxes and duties against Proforma invoice.

**GUARANTEE**

Our equipment are guaranteed for 12 months from date of dispatch.

**VALIDITY**

This offer is valid for 15 days since this day and thereafter subject to confirmation from our side.

Thanking you

Yours faithfully

**For Dharia Switchgear & Controls Pvt Ltd**

Mahesh Katgeri / Ganesh Ghodmode

*Sales Team*