







SaMontec

**Installations for
Flexibility & Design
Freedom**



BOSCH
Invented for life

Fastener Portfolio


Product Range	Model	Model Name	Anchor Material				Application Base Material			ETA
			 Galvanized Steel	 Stainless Steel	 Nylon	 Chemical Bond	 Concrete	 Masonry	 Natural Stone	
Chemical		FIS HB (Highbond)								
		FIS SB (Hybrid)				✓	✓		✓	✓
		FIS EM (Epoxy)				✓	✓		✓	✓
		FIS V (Vinyl Ester)				✓	✓		✓	✓
		FIS P Plus (poly Ester)				✓	✓	✓	✓	✓
		RM			✓	✓	✓		✓	✓
		FHB Dyn				✓	✓		✓	
		RGM	✓	✓			✓	✓	✓	✓
		FIS A	✓	✓			✓	✓	✓	✓
		FTR	✓	✓			✓	✓	✓	
Mechanical		FBN II	✓	✓			✓		✓	✓
		FAZ II	✓	✓			✓		✓	✓
		FH II	✓	✓			✓		✓	✓
		FZA	✓	✓			✓		✓	✓
		FWA	✓				✓		✓	
		FSL	✓				✓		✓	
		EA N M	✓				✓		✓	
		S			✓		✓	✓	✓	
Nylon		UX			✓		✓	✓	✓	
		N	✓	✓	✓		✓	✓	✓	
		SXR	✓	✓	✓		✓	✓	✓	✓
		WST		✓	✓					
Others		PU FOAM					✓			
		PUCLEANER					✓			
Accessories	Dispenser FIS AM 	Dispenser FIS AC 								
	Brush 	Blow Pump 								

Notes: [1] Carbon Steel is galvanised – Zinc plated of 5 microns & Passivated. Stainless steel is of grade A4 & A2.
 [2] The above mentioned loads are guideline working loads for anchors, considering M25 grade non cracked concrete.



Anchor Design Software freely available at www.fischer.de

Injection Mortar FIS V




Hammerest Anchor EA-N



Threaded Rod RG M




Resin Anchor RM




Door Fixing SXR





Bolt FBN II



Injection Mortar FIS EM



Frame Fixing FUR



Marketed by: Bosch Limited, Power Tool Division
Institutional & Industrial Sales
PA-AT Complex, Hosur Road, Adugodi, Bangalore – 560030
Tel: 080-22996092 / 41768352 Fax: 080-22223742



Customer Contact Center
1800 425 8665

Email: bpt@in.bosch.com
www.bosch-pt.co.in
www.fischer.de





Sales Office: Ahmedabad - Tel: 079-66142200 Fax: 079-66142211 **Bangalore** - Tel: 080-22270041 / 22100438 Fax: 080-22225101
Bhubaneswar - Tel: 0674-6628000 Fax: 0674-6628013 **Chandigarh** - Tel: Board - 0172-4587708 Direct - 0172-4587740 Fax: 0172-4587753
Chennai - Tel: 044-28155812 / 28153917 / 28155795 **Ernakulam** - Tel: 0484-2806059 / 2805061 Fax: 0484-2805615
Ghaziabad - Tel: 0120-2833383 Telefax: 0120-2831079 **Guwahati** - Tel: 0361-2131647 / 2131648 **Indore** - Tel: 0731-3075801 / 3075802 / 3075803 Fax: 0731-3075800
Jaipur - Tel: 0141-2387137 / 2387048 / 5105886 Fax: 0141-2387109 **Kolkata** - Tel: 033-40151411 / 40151400 Fax: 033-22275688
Lucknow - Tel: 0522-3264399 / 3208474 / 3208475 Fax: 0522-2637874 **Mumbai** - Tel: 022-24932071 / 72 / 73 / 74 Fax: 022-24973924
New Delhi - Tel: 011-23348260 / 61 / 62 / 63 Fax: 011-23348264 **Pune** - Tel: 020-67254715 / 67254700 Fax: 020-26119004
Raipur - Tel: 0771-4026444 / 4026333 Fax: 0771-4070059 **Secunderabad** - Tel: 040-27990373 / 27990388 Fax: 040-27990338



BOSCH
Invented for life

A|C|T Systems

The Key to New Facade Aesthetics



International Approvals			Application Type			Anchor Diameter (mm)		Load Values (KN)			
ICC	DIBt	Fire	Static	Dynamic	Seismic	Minimum	Maximum	Tension		Shear	
								Minimum	Maximum	Minimum	Maximum
											
	✓			✓		12	24	14.10	28.90	6.70	22.20
			✓			8	30	12.70	157.70	7.20	180.00
✓		✓	✓		✓	8	42	12.70	269.30	7.20	224.20
✓		✓	✓			6	30	6.80	149.50	2.00	112.80
			✓								
			✓			8	30	12.30	140.70	5.90	102.60
	✓	✓	✓	✓				Based on the Bonding Agent Used For Installation			
			✓		✓	6	30				
			✓		✓	8	30				
			✓			8	30				
		✓	✓			6	20	4.00	36.20	3.80	53.60
✓		✓	✓		✓	8	24	7.20	51.80	9.60	68.80
✓		✓	✓		✓	6	24	9.40	68.00	9.40	119.20
		✓	✓		✓	6	22	9.40	51.70	6.40	50.20
			✓			6	20	1.30	13.50	1.30	13.50
			✓			8	20	0.50	4.50	1.00	4.30
			✓			6	20	1.50	9.50	0.50	0.80
			✓			4	20	0.16	3.88	0.16	3.88
			✓			5	14	0.30	1.80	0.3	1.80
			✓			5	10	0.16	0.33	0.16	0.33
			✓			8	10	1.00	1.80	4.20	5.40
			✓								
			✓								

Primary Applications

For structural & non structural applications in Bricks, Concrete & Rock. Base material shall be in wet, dry or saturated conditions.

Service Applications Like Electrical Cable Trays, Mechanical Machines, Plumbing, Fire Fighting, Cladding, HVAC, Lift & Escalators

Domestic Applications, Interiors, Door & Window Frames

For Wash Basin & Toilet Fixing

Construction Gap Filling Application

Dispenser FIS DM SL



Setting Tool EA-ST



Blow out Pump ABG



Drill bit FZUB



[3] Rebar load capacities depends on the yield strength of steel.

[4] Design loads are mentioned for nylon fasteners considering for M20 grade.

We trust fischer
for innovation, safety & range



BOSCH
Invented for life