

Circular: 815(B) - construction

Date: 19.10.2021

Sub.: Installation & purchase of kadis.

This circular is being issued for standardizing the procedure of buying the kadis, fixing kadis & barb wire.

Guideline rates

Sl. No.	Description	Units	Rate
1	Cement kadis of height 6ft. Send requisition to purchase for supply. May be purchased locally for quantities less than 100 nos. Rate includes transportation charges, excludes GST. GST bill not required.	Nos	Rs. 120/-
2	Barb wire. Purchase 12 x 14 guage GI barb wire. 50 kgs bundle will have 400 mtrs of wire. There are different qualities of barb wire. Purchase the best quality from companies like Surana wire.	Bundle	Approx. Rs. 65/- per kg. May vary from time to time.
3	Kadis fixing. Kadis must be fixed at a distance of about 8'. Kadis must be buried to a depth of about 18". Corner kadi must have support with an additional half kadi fixed at 45 ⁰ angle. Similarly, provide a supporting kadi for every 6 kadis.	Nos	Rs. 50/- +/- Rs. 10/-
4	Removal & refixing of kadis	Nos	Rs. 80/- +/- Rs. 10/-
5	Barb wire tying. Tying 5 rows of barb wire with atleast one or two cross wires. Tie using GI wire of 16 guage.	Per kadi	Rs. 50/- +/- Rs. 10/-

Note:

- a. Kadis have been used for the following purpose:
 - i. Serene farms – external fencing and fencing between farmhouses.
 - ii. For marking of new lands being purchased. Here install a 15' gate with RCC columns.
- b. In case of loose soil excavate 18" x 12" x 12" and pour concrete – M15 to fix the kadi properly.
- c. At the time of construction of compound wall remove only kadis that are effecting the RCC columns of compound wall. Remove balance kadis only after construction of all RCC columns for compound wall.

Soham Modi